



自动排水阀 Auto Drain Valve TAD402 Series



Common Specification (共同规格)

Fluid(流体)	Compressed Air(压缩空气)
Max. Operating Pressure(最高使用压力)	1.0Mpa
Min. Operating Pressure(最低使用压力)	0.15Mpa
Proof Pressure(保证耐压力)	1.5Mpa
Ambient&Fluid Temperature(环境和流体温度)	5~60°C
Drain Connection(排水连接)	One touch fitting(Ø6mm), Nipple Rc(PT)1/8
Element Life(滤芯寿命)	When pressure drop reaches at 0.1MPa

How To Order (型号表示方法)

TAD402 - 04 - D

Port Size 接管口径	Accessory 附件	Bowl 材质
02 Rc(PT)1/4 Female Thread(内螺纹)	D Auto Drain, One Touch Fitting(Ø6mm)	Nil(空) PC Bowl
03 Rc(PT)3/8 Female Thread(内螺纹)	Dn Auto drain, Nipple Rc(PT)1/8	M Metal Bowl With Pipe Type Sight Glass
04 Rc(PT)1/2 Female Thread(内螺纹)		MS Metal Bowl With Flat Type Sight Glass
R04 R(PT)1/2 Male Thread(外螺纹)		
G04 G(PF)1/2 Male Thread(外螺纹)		
M30 M30 Male Thread(外螺纹)		

Dimensions(mm)(外形尺寸图(毫米))

